



GARLWAY MACHINERY

GARLWAY MACHINERY

> > >

2014

10

R&D

60,000

3

300

Garlway Machinery



: JW5000



5	()
	30 kW
485	1, 500 2
	: ~2.6, : ~3.2m
-	30 kW
-	, 30 mm 4
-	
-	
-	

: JW3000



	3
	18.5kW
	35
	30rpm
	2200mm x 2200mm x 1600mm
	850kg
	,

: JW500



: 500 L
, 7.5 KW

	500 L
	35 rpm
	7.5 KW
	1500mm × 1400mm

: JW2000



	2000L
	45r/min
	22kW
	2800mm × 2800mm × 2000mm
	1200kg
	: 2 , : 70

: JW1500



，
， 360°
。

	1.5
	1.8，60
	15kW
	360

: JW750



	750 L
	1200 L
	30 - 35m³ / h
	80mm
	2 × 7.5 kw
	7.5 kw
	1.1 kw
	20 r / min
	2650mm × 1315mm × 2180mm
	1.2

Hz s 2 5

: H Z S 2 5



	2 5 (2 0)
	J S 5 0 0
	5 0 . 2 5 K W
	7 2 S
	0 . 5
	0 . 7 5
	P L D 8 0 0 P L D 1 2 0 0 3
	3 . 5
	8 0 0 L 1 2 0 0 L
	5 0 m m
	, : ± 2 % ; , , : ± 1 %
	1 . 5 - 3 . 8 m
	5 0 . 2 5 K W
	1 1 6 9 3 m m × 1 3 0 6 0 m m × 1 7 2 4 5 m m
	1 7 5 0 0 k g

	JS500
	/

Hzs90

: HZS90



HZS90

	90 /
	JS1500 , 2×30kW , 1500L , 60S
	PLD2400 , 2400L , 4
	80mm
-	(0-900)±1%kg
-	(0-50)±1%kg
-	0-5000±2%kg
	3×100t
	3.8 4.2
	164kW
	24 () x 10 () x 18 ()
	65000kg
	90
	JS1500

--	--

J z c 1 0 0 0

: J Z C 1 0 0 0



Discover the high-performance for construction sites, road factories. Features 1600L feeding discharge, and precise mixing efficiency today!

Parameter	Value / Description
Feeding Capacity	1600L
Discharge Capacity	1000L
Productivity	25 - 30m³ / h
Mixing Drum Speed	13r / min
Maximum Particle Size	100mm
Water Supply Error	2%
Discharge Height	2500mm
Application Fields	General construction site, Road and bridge project, Concrete component factory
Selling Points	Sturdy and durable structure, Good mixing quality, Easy operation, Convenient

J s 3 0 0 0

: J S 3 0 0 0



J S 3 0 0 0 :

, . !

	6 0 0

--	--

	3

3 /

--	--

--	--

J z c 5 0 0

: J Z C 5 0 0



J Z C 5 0 0

	J Z C 5 0 0
	5 0 0 L
	8 0 0 L
	1 8 ~ 2 0 m ³ / h
	6 0 mm
	1 3 r / m i n
	2 0 k m / h
	7 . 5 k w
	5 . 5 K W
	0 . 5 5 k w
	2 4 0 0 k g
(x x)	3 5 0 0 x 2 2 0 0 x 3 2 0 0 mm

J z c 4 0 0

: J Z C 4 0 0



J Z C 4 0 0

J Z C 3 0 0	N o r m a l	4 5 #		,
J Z C 3 5 0		4 5 #		,
J Z C 4 0 0		4 5 #		
J Z C 5 0 0		4 5 #		,
J Z C 7 5 0		4 5 #		,
J Z C 1 0 0 0		4 5 #		,
J Z C 1 5 0 0		4 5 #		,

Hzs35

: HZS35



	35 / (: 25 - 35 /)
	JS750
	30KW
	1200L
	0.75
	75S
	PLD1200 3
	36
	1200L
	3
	: 60mm , : 80mm
	0 - 250kg (: 1kg)
	0 - 200kg (: 1kg)
	2.82m
	3.8m ()
	74.9KW
	4951mm × 3650mm × 6225mm

	JS 750

	50,000
--	--------

--	--

: JW6000

: 6 m³ ,



	6
	3.7 kW
	4105 4
	485 1 , 500 2
	2.8 , 1
	3 , 2 , 180° 1

Hzs180

: HZS180



	180
	JS3000MAO4500/3000SDSHO
	110kW2×55kW
	3
	PLD4800
	4800L
	4~6
(, , , ,)	
()	0~1500kg(±1%)
()	0-50kg(±1%)
	4
	200
	180
	JS3000

PLC

--	--

J s 1 5 0 0

: J S 1 5 0 0



J S 1 5 0 0

	J S 1 5 0 0
	1 . 5
	()

Hzs 50

: HZS50



	50 / (: 30 - 35 /)
	JS1000
	2 × 18.5 KW
	1000 L
	1500 L
	72 S
	PLD1600
	3.5 × 3
	1600 L
	3
	: 80 mm
	0 - 600 kg , ± 1%
	0 - 300 kg , ± 1%
	2.58 m
	2.7 m 3.8 m
	85.0 KW
(2.7 m)	10867 mm × 4070 mm × 6560 mm
(3.8 m)	17012 mm × 4070 mm × 8400 mm
(2.7 m)	14870 kg
(3.8 m)	17570 kg

: J Z C 3 0 0



Portable cement mixer for co
and DIY. High performance, e
durable design.

Parameter	Specification
Capacity	Feeding: 480L, Discharging: 300L
Productivity	9-12 m ³ /h
Motor Power	Mixing: 4KW, Lifting: 4KW, Pump: 0.55KW
Stirring Drum Speed	17 r/min
Maximum Aggregate Size	60 mm
Overall Dimension	2376 × 1990 × 2750 mm
Overall Weight	1650 kg

Application Field	Description
General Construction	Concrete mixing for civil and commercial buildings, rural self-built houses, Road and Bridge Project
Concrete Component Fa	Production of small concrete components like blocks and precast panels

Product Selling Point	Description
Performance	Self-falling double-cone reversing discharging, homogeneous concrete in 35-4
Structure	Tires and towing frame for easy transfer, adjustable height legs for stabili
Operation	Water supply system with motor, pump, regulating valve, and time relay contr
Quality	Designed and manufactured according to GB/T9142-2000 standard, efficient, hi

: JW4000



	: 5.3 , : 4
	3.7 kW
	: 2.6 , : 3.2

: J Z C 3 5 0



J Z C 3 5

	J Z C 3 5 0
	() , ()

H z s 1 2 0

: H Z S 1 2 0



H Z S 1 2 0 :

	1 2 0 /
	J S 2 0 0 0
	2 × 3 7 kW
	3 2 0 0
	2
	P L D 3 2 0 0
	3 2 0 0
	2 ~ 4
	2 0
	1 2 0 mm
(, , ,)	± 1 %
()	± 2 %
	2 × 2 0 0
	3 . 8 4 . 2
	1 4 5 - 2 0 9 . 5 kW
	9 0 × 1 0 ³ kg

	1 2 0
	P L C

: JS750



	750 L
	1200 L
	30 - 35 m ³ / h
	30 kW () + 7.5 kW ()
	80 mm ()
	1.6 m / 2.7 m / 3.8 m ()

J s 2 0 0 0

: J S 2 0 0 0



	J S 2 0 0 0
	2

J s 1 0 0 0

: J S 1 0 0 0



J S

	J S 1 0 0 0

J d y 3 5 0

: J D Y 3 5 0



	18 - 21

: G J W 3 5 0



	3 5 0 L
	2 1 r / m i n
	5 . 5 k W
	€ 1 2 0 0 × 1 4 0 0 m m
	3 5 0 k g



Garlway Machinery

55

