GARLWAY MACHINERY

,

,

,

GARLWAY MACHINERY

> > >

2014 ,

. ,

. 10

R&D

. 60,000 3 300

. , , , ,

Garlway Machinery

.

.

: JW1500

,

. , 360°

. .

	1.5
	1.8 , 60
	15kW
	360

: JW750

.

.

!

	750L
	1200L
	30 - 35m³/h
	80mm
	2×7.5kw
	7.5kw
	1.1kw
	20r/min
	2650mm×1315mm×2180mm
	1.2

: JZC750

,

. , , 1

.

	18-22m3/h
	, , , , , , , , ,
	BV, ISO
	(, ,) 1
	, , 2
	, , ,

: JW500

: 500L

, 7.5KW . ,

.

.

	500L
	35rpm
	7.5KW
	1500mm × 1400mm
	, , , , , , . ,
	. , , , .
	: , , , , , .
	. . ,
	, . .

Jdy350

: JDY350

,

. , ,

!

, , .	
	, .
, , .	
	, , .
	, , 18-21 .
, .	
	, .
, , , , .	
	.

.

: HZS25

. , ,

. .

	25 (20)
	JS500
	50.25KW
	72S
	0.5
	0.75
	PLD800 PLD1200 3
	3.5
	800L 1200L
	50mm
	, : ±2%; , , , : ±1%
	1.5-3.8m
	50.25KW
	11693mm × 13060mm × 17245mm
	17500kg

	, ,
	, ,
	, ,
	,

,	,
	JS500 ,
	, , , ,
	/
	,
,	,

: JW3000

,

.

.

	3
	18.5kW
	35
	30 rpm
	2200mm x 2200mm x 1600mm
	850kg
	,

: JW2000

,

.

.

.

	2000L
	45r/min
	22kW
	2800mm × 2800mm × 2000mm
	1200kg
	: 2 , : 70

Hzs180

: HZS180

.

, ,

.

!

	180
	JS3000 MAO4500/3000SDSHO
	110kW 2×55kW
	3
	PLD4800
	4800L
	4 ~ 6
(, , , ,)	
( )	0~1500kg(±1%)
( )	0-50kg(±1%)
	4
	200

	, ,
	, , ,
	, ,

	180 .
	JS3000 .

P L C

	.

, , .

Jdc350

: JDC350

,

JDC350

.

.

	JDC350
	JDC
	, , ,
	(, ,), , , ,
	, , , , ,
	, , , , ,
	, , ,
	, , , ,
	, , ,
	, , , ,
	,
	, ,
	, , , ,

Hzs75

: HZS75

, ,

HZS75

.

	75 /
	JS1500 , 30×2kW, 1.5 , 2.4
	PLD2400 , 4 , , 2400L, 80mm
	: ±2%, , , , : ±1%
	3.8
	24350mm x 10595mm x 18704mm
	120kW
	60

	,
	,
	, ,

	: 75 /
	JS1500 .
	, ,
	.
	, ,

Hzs90

: HZS90

,

HZS90 .

, . !

	90 /
	JS1500 , 2×30kW, 1500L, 60S
	PLD2400 , 2400L, 4
	80mm
-	(0-900)±1%kg
-	(0-50)±1%kg
-	0-5000±2%kg
	3×100t
	3.8 4.2
	164kW
	24 ( ) x 10 ( ) x 18 ( )
	65000kg

	, .
	, .
	, .
	,

	90 .
	JS1500 .
	.

, ,

	,

, ,

Hzs 50

: HZS50

,

.

.

	50 / (: 30-35 /)
	JS1000
	2 × 18.5KW
	1000L
	1500L
	72S
	PLD1600
	3.5 × 3
	1600L
	3
	: 80mm
	0-600kg, ±1%
	0-300kg, ±1%
	2.58m
	2.7m 3.8m
	85.0KW
(2.7m)	10867mm × 4070mm × 6560mm
(3.8m)	17012mm × 4070mm × 8400mm
(2.7m)	14870kg
(3.8m)	17570kg

	, .
	, .
	, .
	, ,

	50
	JS1000 , , .
	.
	, ,

Hzs35

: HZS35

. , ,

. !

	35 / (: 25-35 /)
	JS750
	30KW
	1200L
	0.75
	75S
	PLD1200 3
	36
	1200L
	3
	: 60mm, : 80mm
	0-250kg(: 1kg)
	0-200kg(: 1kg)
	2.82m
	3.8m( )
	74.9KW
	4951mm × 3650mm × 6225mm

	,
	,

,

	JS750 .
	, , , .
	, 50,000 .
	, ,
	, ,

: JW6000

: 6m³ ,

, . , ,

.

	6
	37kW
	4105 4
	485 1 , 500 2
	2.8 , 1
	3 , 2 , 180° 1

Jzc1000

: JZC1000

Discover the high-performanc
for construction sites, road
factories. Features 1600L fe
discharge, and precise mixin
efficiency today!

Parameter	Value / Description
Feeding Capacity	1600L
Discharge Capacity	1000L
Productivity	25 - 30m³/h
Mixing Drum Speed	13r/min
Maximum Particle Si	100mm
Water Supply Error	2%
Discharge Height	2500mm
Application Fields	General construction site, Road and bridge project, Concrete component factor
Selling Points	Sturdy and durable structure, Good mixing quality, Easy operation, Convenient

: JW5000

	5 ( )
	30kW
	485 1 , 500 2
	: ~2.6 , : ~3.2m
	, , , , , , , . , , ,
-	30kW .
-	, , 30mm 4
-	
-	, ,
-	, , , , .

: JW400

: 400L , 5.5KW

. ,

.

	400L
	19 rpm
	5.5KW
	1200mm × 1200mm
	1.2 ( )

	, , , , , , . , ,
	, , , , .

	, , , , .
	, , , . .
	. .

: JZC300

Portable cement mixer for co
and DIY. High performance, e
durable design.

Parameter	Specification
Capacity	Feeding: 480L, Discharging: 300L
Productivity	9-12 m³/h
Motor Power	Mixing: 4KW, Lifting: 4KW, Pump: 0.55KW
Stirring Drum Speed	17 r/min
Maximum Aggregate Siz	60 mm
Overall Dimension	2376 × 1990 × 2750 mm
Overall Weight	1650 kg

Application Field	Description
General Construction	Concrete mixing for civil and commercial buildings, rural self-built houses,
Road and Bridge Proje	Concrete mixing for road laying, bridge construction, road base, bridge pier
Concrete Component Fa	Production of small concrete components like blocks and precast panels

Product Selling Point	Description
Performance	Self-falling double-cone reversing discharging, homogeneous concrete in 35-4
Structure	Tires and towing frame for easy transfer, adjustable height legs for stabili
Operation	Water supply system with motor, pump, regulating valve, and time relay contr
Quality	Designed and manufactured according to GB/T9142-2000 standard, efficient, hi

: JZC350

JZC35

. , ,

.

.

	JZC350
( ), ( )	
,	
,	
, , , ,	
, , , , , , ,	

Jzc400

: JZC400

JZC400

.

. .

!

JZC300	Normal	45 #		,
JZC350		45#		,
JZC400		45#		
JZC500		45#		,
JZC750		45#		,
JZC1000		45#		,
JZC1500		45#		,

Hzs120

: HZS120

HZS120 :

, ,

	120 /
	JS2000
	2 × 37kW
	3200
	2
	PLD3200
	3200
	2 ~ 4
	20
	120mm
(, , ,)	±1%
( )	±2%
	2×200
	3.8 4.2
	145-209.5 kW
	90 x 10^3 kg

	, ,
	, , ,
	, ,

	1 2 0
	,
	,
	P L C
	,

, , , .

: JW4000

, ,

.

, . !

	: 5.3 , : 4
	37kW
	: 2.6 , : 3.2
	, , , , , , ,
	, , ,
	, , , , ,

Jzc500

: JZC500

JZC500

	JZC500
	500L
	800L
	18~20 m³/h
	60mm
	13 r/min
	20km/h
	7.5kw
	5.5KW
	0.55kw
	2400kg
(x x)	3500x2200x3200mm

Js500

: JS500

: , ,

.

.

	, , , ,
	PLD , HZS25 .
	,
	-
	.
	, ,
	1.5m, 3.8m
	11
	, ISO SGS

Jw1000

: JW1000

,

.

,

.

	1000L, 1200-1400L
	45r/min
	15kw
	ϵ1600×2000mm ϵ1800×1600mm
	650kg

	(: , ,) .
	(: , ,) .
	,
	, ,

	, , , .
	, ,
	, ,
	/
	(: ,)
	, ,

Js3000

: JS3000

JS3000 :

, .

. !

	600 , .
	, . ,
	, - .
	.

	3 , , , , .
	3 / .
	, , , .
	.
	, , .

Garlway Machinery

55 .

garlway@16 https://garlwa