



GARLWAY MACHINERY

GARLWAY MACHINERY

> > >

2014

10

R&D

60,000

3

300

Garlway Machinery



: JW5000



5	()
	30 kW
485	1, 500 2
	: ~2.6, : ~3.2m
-	30 kW
-	, 30 mm 4
-	
-	
-	

: G J W 3 5 0



	3 5 0 L
	2 1 r / m i n
	5 . 5 k W
	€ 1 2 0 0 × 1 4 0 0 m m
	3 5 0 k g

: JW3000



	3
	18.5kW
	35
	30rpm
	2200mm x 2200mm x 1600mm
	850kg
	,

Hzs35

: HZS35



	35 / (: 25 - 35 /)
	JS750
	30KW
	1200L
	0.75
	75S
	PLD1200 3
	36
	1200L
	3
	: 60mm , : 80mm
	0 - 250kg (: 1kg)
	0 - 200kg (: 1kg)
	2.82m
	3.8m ()
	74.9KW
	4951mm × 3650mm × 6225mm

	JS 750

	50,000
--	--------

--	--

J z c 4 0 0

: J Z C 4 0 0



J Z C 4 0 0

J Z C 3 0 0	N o r m a l	4 5 #		,
J Z C 3 5 0		4 5 #		,
J Z C 4 0 0		4 5 #		
J Z C 5 0 0		4 5 #		,
J Z C 7 5 0		4 5 #		,
J Z C 1 0 0 0		4 5 #		,
J Z C 1 5 0 0		4 5 #		,

: JW500



: 500 L
, 7.5 KW

	500 L
	35 rpm
	7.5 KW
	1500mm × 1400mm

H z s 1 2 0

: H Z S 1 2 0



H Z S 1 2 0 :

	1 2 0 /
	J S 2 0 0 0
	2 × 3 7 kW
	3 2 0 0
	2
	P L D 3 2 0 0
	3 2 0 0
	2 ~ 4
	2 0
	1 2 0 mm
(, , ,)	± 1 %
()	± 2 %
	2 × 2 0 0
	3 . 8 4 . 2
	1 4 5 - 2 0 9 . 5 kW
	9 0 × 1 0 ³ kg
	,
	,
	,

	1 2 0
	P L C

: JW6000



: 6 m³ ,

	6
	3.7 kW
	4105 4
	485 1 , 500 2
	2.8 , 1
	3 , 2 , 180° 1

--	--

: JW1500



，
， 360°
。

	1.5
	1.8，60
	15kW
	360

J z c 1 0 0 0

: J Z C 1 0 0 0



Discover the high-performance for construction sites, road factories. Features 1600L feeding discharge, and precise mixing efficiency today!

Parameter	Value / Description
Feeding Capacity	1600L
Discharge Capacity	1000L
Productivity	25 - 30m³ / h
Mixing Drum Speed	13r / min
Maximum Particle Size	100mm
Water Supply Error	2%
Discharge Height	2500mm
Application Fields	General construction site, Road and bridge project, Concrete component factory
Selling Points	Sturdy and durable structure, Good mixing quality, Easy operation, Convenient

: JW2000



	2000L
	45r/min
	22kW
	2800mm × 2800mm × 2000mm
	1200kg
	: 2 , : 70

: JW750



	750 L
	1200 L
	30 - 35m³ / h
	80mm
	2 × 7.5 kw
	7.5 kw
	1.1 kw
	20 r / min
	2650mm × 1315mm × 2180mm
	1.2

Hz s 2 5

: H Z S 2 5



	2 5 (2 0)
	J S 5 0 0
	5 0 . 2 5 K W
	7 2 S
	0 . 5
	0 . 7 5
	P L D 8 0 0 P L D 1 2 0 0 3
	3 . 5
	8 0 0 L 1 2 0 0 L
	5 0 m m
	, : ± 2 % ; , , : ± 1 %
	1 . 5 - 3 . 8 m
	5 0 . 2 5 K W
	1 1 6 9 3 m m × 1 3 0 6 0 m m × 1 7 2 4 5 m m
	1 7 5 0 0 k g

	JS500
	/

Hzs180

: HZS180



	180
	JS3000MAO4500/3000SDSHO
	110kW2×55kW
	3
	PLD4800
	4800L
	4~6
(, , , ,)	
()	0~1500kg(±1%)
()	0-50kg(±1%)
	4
	200
	180
	JS3000

	PLC

J d c 3 5 0

: J D C 3 5 0



J D C 3 5 0

	J D C 3 5 0
	J D C
	(, ,) , , , ,
	, , , , , , , ,
	, , , , , , , ,
	, , , , , , , ,
	, , , , , , , ,
	, , , , , , , ,
	, , , , , , , ,

Hzs 50

: HZS50



	50 / (: 30 - 35 /)
	JS1000
	2 × 18.5 KW
	1000 L
	1500 L
	72 S
	PLD1600
	3.5 × 3
	1600 L
	3
	: 80 mm
	0 - 600 kg , ± 1%
	0 - 300 kg , ± 1%
	2.58 m
	2.7 m 3.8 m
	85.0 KW
(2.7 m)	10867 mm × 4070 mm × 6560 mm
(3.8 m)	17012 mm × 4070 mm × 8400 mm
(2.7 m)	14870 kg
(3.8 m)	17570 kg



Garlway Machinery

55

